

Energy Efficiency Information

Attribute	Symbol	Value		Units
Model Identification		MH600X MH600BK MH700X MH700BK	MH900X MH900BK MH1000X MH1000BK	
Annual Energy Consumption	AEC_{Hood}	15.1	15.5	kWh
Time Increase factor	f	1.7	1.7	
Fluid Dynamic Efficiency	FDE_{Hood}	8.7	8.7	
Energy Efficiency Index	EEl_{Hood}	52.8	53.8	
Measured Airflow at Best Efficiency Point	Q_{BEP}	181.9	181.9	m ³ /h
Measured Pressure at Best Efficiency Point	P_{BEP}	39	39	Pa
Maximum Airflow	Q_{MAX}	285.1	285.1	m ³ /h
Measured Electric Power at Best Efficiency Point	W_{BEP}	22.6	22.6	W
Nominal Lighting Power	WL	1.5	2	W
Average Illumination of the lighting system on the cooking surface	E_{Middle}	74	221	Lux
Measured Power Consumption in standby	P_s	--	--	W
Measured Power Consumption off mode	P_o	0.0	0.0	W
Noise level	L_{WA}	52	52	dBA
Grease Filter Efficiency	GFE_{Hood}	57.8(E)	57.8(E)	%
Lamp Efficiency	LE_{Hood}	49(A)	76(A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. MONTPELLIER reserve the right to change specifications without prior notice.